

Approved product certificate

No.: 05842-1


X-Module A/S, Test lab. Facility, Lilleringvej 24, 8462 Harlev

Product licenced to: X-Module A/S, Lilleringvej 14, DK-8462 Harlev

Product manufactured by: X-Module A/S, Lilleringvej 24, DK-8462 Harlev J

Applicant of testing: Mr. Steen Kreiberg
Date of testing: 29.05.2018
Certificate file reference: HSC/SBK/Testlab/3819.0199
Date of issue: 01.06.2018
Valid until: 31.05.2020

Test facility:



Signature:

Product description - dimensions:

- Single square truss system: "X-15 EXPOWIRE" 05xxx (Reg. trademark) (Pat. ped, EUR design)
- Dimensions: Square truss 150 x 150 mm (outer dimensions).
- Cord members: \varnothing 20 mm
- Bracing members: \varnothing 8 mm
- Truss units lengths: 0,15 - 2,4 m

Product description - materials:

- Supportive elements: Aluminium AlMgSi0,5
- Truss elements: 30% fibre reinforced composite.

Product components tested according to:

- DIN 4113; ISO 527-1/-2

Flammability:

- The products qualify for DIN 4102 - B1; ISO 1210/UL94-V0

Additional information:

- Truss units assembled with connecting element (connector) or cubic connecting element (cube) is disregarded by test.
- Single individual units only.

Load data, structure:

- Allowable normal force on main cord: 250 N
- Allowable normal force on bracing members: 25 N

Load data, Truss units:

Truss length (m)	Undistributed load (Kg)	Distributed load (Kg)
0,6	100	100
1,2	100	100
1,8	100	100
2,4	75	100

Max. load on free span 6,0 m: 12 kg (distributed load).
Ex: 4 spot-lights - weight: 3 kg / each.

- Modules must be connected to verticals in both ends.
- Max. free span 6,0 m.
- Spans must be supported at both ends.
- Loads are in addition to self weight loads.
- Only use standard connectors for truss.
- Load table only applies to simple beam load case.